

Skylight Shading Systems



Application Chart

Operation	Dimensions					Application	Profile			Features	Fitting Options		Fitting Surfaces		System
	Number of bays	max.	max.	m ² max.	kg max.		Sloping	Profile Number	Min. Bending Radius (mm)		Radio Control	Ceiling Fix	Wall Fix	Wood	
	1	2.5m	6m	15m ²	10kg	●	2191	200	●	●	●	●	●	2190	
	2	3m	6m	18m ²	10kg										
	1	3m	6m	18m ²	25kg	●	2191	200	●	●	●	●	●	2195	
	2	6m	6m	30m ²	25kg										
	3	6m	6m	36m ²	25kg										
	—	4m	6.5m	18m ²	40kg*	●	8601	—	●	●	●	●	●	8600	
	—	3m	12m	36m ²	67kg*	●	8801	—	●	●	●	●	●	8800	

i * Total system weight with fabric.
 Note: System 8700 – maximum 3m between side profiles plus up to 1m cantilever each side.



www.silentgliss.co.uk

www.silentglissglobal.com

Silent Gliss Ltd
Pyramid Business Park
Poorhole Lane
Broadstairs
Kent
CT10 2PT
Great Britain

Tel: +44 (0) 1843 863571
Fax: +44 (0) 1843 864503
info@silentgliss.co.uk

Silent Gliss Global Ltd
Pyramid Business Park
Poorhole Lane
Broadstairs
Kent
CT10 2PT
Great Britain

Tel: +44 (0) 1843 874250
Fax: +44 (0) 1843 874457
info@silentglissglobal.com