

Roller Blinds



Application Chart

Operation	Dimensions					Applications	Profile		Features / Options					Fitting Options			Fitting Surfaces			System	
	min.	max.	max.	m ² max.	kg max.		Heavy Duty	Profile Number	Profile Diameter (ø mm)	Connected Systems (one Drive)	Side-by-Side Systems (two Drives)	Side Guides available	Fascia Cover available	Stop Controller available	Ceiling Fitting	Wall Fitting	Recess Fitting	Wood	Concrete		Suspended Ceiling
	30 cm	2 m	3 m	6 m ²	2.2 kg		4227	ø32	●	●			●	●	●	●	●	●	●	●	4900
	25 cm	1.4 m	3 m	4.2 m ²	1 kg		10533	ø25		●				●	●	●	●	●	●	●	4905
	25 cm	2.4 m	3 m	7.2 m ²	3 kg		10531	ø41	●	●			●	●	●	●	●	●	●	●	4910
	120 cm	3.3 m	4 m	10 m ²	7 kg	●	4701	ø55	●		●	●	●	●	●	●	●	●	●	●	4830
	45 cm	3 m	5 m	15 m ²	12.5 kg	●	4460	ø60	●	●			●	●	●	●	●	●	●	●	4840
	45 cm	4.5 m	5 m	15 m ²	12.5 kg		4480	ø80													
 DC 12V	60 cm	2.4 m	4 m	9.6 m ²	2.5 kg		10532	ø41						●	●	●	●	●	●	●	4955
 230V	61 cm	2.4 m	4 m	9.6 m ²	5.5 kg		10532	ø41	●	●	●			●	●	●	●	●	●	●	4960
 230V	65 cm	3 m	5 m	15 m ²	23 kg	●	4460	ø60	●	●			●	●	●	●	●	●	●	●	4450
	65 cm	4.5 m	5 m	20 m ²	23 kg		4480	ø80													



www.silentgliss.com.au

Unit 5, 2-8 South Street
Rydalmere NSW 2116
Australia
Tel: +61 2 9810 4300
Fax: +61 2 9810 4311
info@silentgliss.com.au